

Did you know you can use your management port as an uplink port?

Please see below the instructions on how to do this.

It's recommended that this should be a temporary measure while you purchase an SFP+ module; the use of an SFP+ module will make sure your bandwidth requirements are fully taken care of.

Note: the below assumes that you have not deleted the existing management VLAN of 1001. If you have, please create that VLAN first before continuing with the below.

Management Port into an Uplink Port

configure terminal
interface GigabitEthernet 1/25
switchport access VLAN 1

Management Port back to default configuration

configure terminal
interface GigabitEthernet 1/25
switchport access vlan 1001

You can look to purchase any of the below accessories at any distributor of our products.

SFP Transceivers: *Accessory Product Details*

NVT Phybridge offers the below industry standard SFP+ modules for use with the CLEER24-10G. These modules have been produced and tested for 100% compatibility by NVT Phybridge. They are the recommended modules NVT Phybridge suggests be used with our managed switches. Please see www.nvtpybridge.com for full technical specifications. Please note to use the CLEER24-10G you must have a compatible SFP+ module (not included), this allows for uplink connection to your network.

NV-GLC-SX-MMD

- Speed: 1.25 Gb/s
- Wavelength: 850nm VCSEL
- Distance: up to 550m on 50/125µm MMF
- Operating temperature: 0°C to 70°C (32°F to 158°F)

NV-GLC-LH-SMD

- Speed: 1.25 Gb/s
- Wavelength: 1310nm FP
- Distance: up to 20km on 9/125µm SMF
- Operating temperature: 0°C to 70°C (32°F to 158°F)

NV-GLC-EX-SMD

- Speed: 1.25 Gb/s
- Wavelength: 1310nm DFB
- Distance: up to 40km on 9/125µm SMF
- Operating temperature: 0°C to 70°C (32°F to 158°F)

NV-SFP-RJ45

- Speed: 1.25 Gb/s
- Rate category: 10/100/1000 Base
- Distance: up to 100m
- Operating temperature: 0°C to 70°C (32°F to 158°F)

NV-SFP-10G-SR-LC

- Speed: 10 Gb/s
- Wavelength: 850nm DFB
- Distance: up to 300m on 50/125µm MMF
- Operating temperature: 0°C to 70°C (32°F to 158°F)

NOTE: This module is SFP+ and is only compatible with the 10G line of switches

Phone: 888.901.3633
905.901.3633

Web: www.nvtpybridge.com

